



SHURHOLD POLISHERS

Dual Action and Rotary Polishers

EDMO Distributors



The Dual Action Polisher was designed to allow users to achieve the same high gloss, professional finish that the pros do with a rotary buffer/polisher, but in a unit that less-experienced, everyday users can operate with the same effectiveness. Traditional rotary polishers have a larger wheel spinning at a high rpm, which means the operator's technique is important as to avoid burns and swirls. The Shurhold polisher's dual action, 6-inch oscillating head eliminates these issues and allows anyone to get the same great finish, without burns or swirls.

The Dual Action Polisher Pro is a more powerful version of the Shurhold Dual Action Polisher, the PRO features an XL, 21 mm orbit. The random orbit motion will still protect your finish from burning and swirling while giving you the professional results you desire.

The Pro Rotary Polisher is a professional grade tool designed to quickly remove heavy oxidation and correct surface imperfections. Built with EZ Clean Mesh Intake Vents, EZ-Change Carbon Brushes, and a soft start trigger. Prior experience with a rotary tool is recommended before using this machine. This super powerful true Rotary Polisher cuts, polishes, and buffs to bring out a mirror-like finish in even the dullest surface.

DESCRIPTION	EDMO#
Dual Action Polisher	3100S
Dual Action Polisher Pro	3500S
Pro Rotary Polisher	3400S

ACCESSORIES

Each polisher has multiple pad/attachment options. Call or visit edmo.com for full selection

*CALL OR LOGIN FOR DEALER PRICING

Features:

- Quick change backing plate (5" Dual Action, 6" Dual Action Pro, 7" Rotary)
- Variable speed (Dual Action 2500-6500 OPM, Dual Action Pro 1800-4800 OPM, Rotary 600-3200 RPM)
- Locking ON button (Pro models)
- Thumb controlled variable speed dial (Pro models)
- Multiple ergonomic gripping styles
- EZ change carbon brush ports (Pro models)
- 20 ft power cord
- Canvas storage bag

SPECIFICATIONS

Weight	(3100) - 4.8 lb, (3500) - 5.2 lb, (3400) - 6.6 lb
Rated voltage	120 VAC
Rated current	(3100) 4.2 A, (3500) - 7.5 A (3400) -12 A
Rated power	(3100) 500W, (3500) 900W, (3400) 1400W
Orbit diameter	(3100) 5/16" (8mm), (3500) 13/16" (21mm)
Frequency	60 Hz
Thread size	5/16"-24, Pro Models 5/8" - 11
Quick change backing plate	(3100) 5" (127mm) (3500) 6" (152mm), (3400) 7" (178mm)
Power cord	20 feet (6m)